

**LG CHEMICAL LTD**

20 YOIDO-DONG, YONGDUNGPO-GU, SEOUL 150-721 KR

**XR474****Acrylonitrile Butadiene Styrene (ABS), furnished as pellets**

<b>Color</b>	<b>Min Thk (mm)</b>	<b>Flame Class</b>	<b>HMI</b>	<b>HAI</b>	<b>RTI Elec</b>	<b>RTI Imp</b>	<b>RTI Str</b>
<b>ALL</b>	<b>3.0</b>	<b>HB</b>	-	-	<b>60</b>	<b>60</b>	<b>60</b>

Comparative Tracking Index (CTI): -

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate (HVTR): -

High Volt, Low Current Arc Resis (D495): -

Dielectric Strength (kV/mm): -

Volume Resistivity (10<sup>x</sup> ohm-cm): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2000-07-12

Last Revised: 2006-05-02

Underwriters Laboratories Inc®

